

ID Material: 9 Rble: R. Antich Revision: 6

Last updated: 06/10/2022

Barri del migdia S/N - E 08396 Sant Cebrià de Vallalta (Barcelona - Spain) sauleda@frenossauleda.com Tel. (+ 34) 93 763 11 20 Fax (+ 34) 93 763 10 61

VH-03

VH-03 is the last generation of Sauleda clutch facings, with similar friction properties but higher stiffness. Smooth behaviour and very high temperature resistance. VH-03 is a woven material with glass fibre and is reinforced with copper. This clutch facing performs with very stable coefficient and resists temperature with a minimum wear.

## Material data

Friction Properties (according graphics)		
Static Friction Coefficient (15bar, from box):	0.42±0.05	μ
Static Friction Coefficient (15bar, 100ºC):	0.44±0.05	μ
Dynamic Friction Coefficient:	see charts	
Wear Rate:	see charts	
Tº Fading:	>350	°C
Physical properties		
Hardness (DIN53505):	85±5	Shore-D
Specific Gravity (ASTM D792):	1.95±0.05	gr/cm3
Ignition Loss (ASTM D7348):	40±2	%
Thermal Conductivity (ASTM E1952):	0.33±0.03	W/m°K
Mechanical properties		
Compressive Strength (ISO 844:2014):	120±5	N/mm²
Burst Resistant (200 x 137 x 3,5) 200°C:	12000±100	RPM
Recommended Working Values		
T° Max. Continuous Operation:	250	°C
T° Max. Intermittent Operation:	350	°C

Material	tvpe:	Woven	varn
materia	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		<i>j</i> α

## Appearance / Formats









## **Applications**

Heavy vehicle clutches - Trucks clutches - Vehicles clutches


Price Level : € €

ilice Level . C C C

Reach (EC)1907/2023 - RoHS 2015/863/EU: Compliance

## Others

Recommended Mating Surface:	Perlitic cast iron, hardness HB150-200
Recommended Adhesives:	Thermosetting adhesive
Oil Resistant:	Yes



Rubbing speed, temperature and pressure are related. Changing any values will change other. The values shown represent typical conditions, but are not ultimate limits of the material.